

Použít šrouby s válcovou hlavou
DIN EN ISO 4762 M8.

B

Technical drawing of a mechanical part B, showing a front view and a side view.

Front View:

- Overall length: l_1
- Overall width: l_2
- Width of the central section: b_2
- Width of the side section: b_1
- Four circular holes are located in the central section, with a diameter of $\varnothing 9$.
- A textured area is present on the left side of the central section.
- A dimension of 25 is indicated for the distance from the bottom edge to the center of the holes.

Side View:

- Overall width: 10
- Chamfer: 15°
- Radius: R5
- Hole diameter: $\varnothing 9$
- Distance from the edge to the hole: 15
- Chamfer: $3 \times 45^\circ$
- Hole diameter: 12, with a tolerance of $0,02$
- Surface texture symbol: $\sqrt{\text{ }}$ 0,02

Kluzná deska, Bronzové s grafitovými tělísky, VDI 3357

2960.81. Kluzná deska, Bronzové s grafitovými tělísky, VDI 3357

Objednací číslo	Tvar	b ₁	b ₂	l ₁	l ₂	l ₃	l ₄	Počet otvorů
2960.81.030.080	A	30	-	80	55	-	-	2
2960.81.030.100	A	30	-	100	75	-	-	2
2960.81.030.125	A	30	-	125	100	-	-	2
2960.81.030.160	A	30	-	160	135	-	-	2
2960.81.030.200	A	30	-	200	175	-	-	2
2960.81.030.225	A	30	-	225	200	-	-	2
2960.81.030.250	C	30	-	250	85	165	225	4
2960.81.030.260	C	30	-	260	85	175	235	4
2960.81.030.280	C	30	-	280	85	195	255	4
2960.81.030.300	C	30	-	300	105	195	275	4
2960.81.030.320	C	30	-	320	105	215	295	4
2960.81.040.080	A	40	-	80	55	-	-	2
2960.81.040.100	A	40	-	100	75	-	-	2
2960.81.040.125	A	40	-	125	100	-	-	2
2960.81.040.160	A	40	-	160	135	-	-	2
2960.81.040.200	A	40	-	200	175	-	-	2
2960.81.050.080	A	50	-	80	55	-	-	2
2960.81.050.100	A	50	-	100	75	-	-	2
2960.81.050.125	A	50	-	125	100	-	-	2
2960.81.050.160	A	50	-	160	135	-	-	2
2960.81.050.200	A	50	-	200	175	-	-	2
2960.81.050.225	A	50	-	225	200	-	-	2
2960.81.050.250	C	50	-	250	85	165	225	4
2960.81.050.300	C	50	-	300	105	195	275	4
2960.81.050.350	C	50	-	350	125	225	325	4
2960.81.050.400	C	50	-	400	145	255	375	4
2960.81.060.080	A	60	-	80	55	-	-	2
2960.81.060.100	A	60	-	100	75	-	-	2
2960.81.060.125	A	60	-	125	100	-	-	2
2960.81.060.160	A	60	-	160	135	-	-	2
2960.81.060.200	A	60	-	200	175	-	-	2
2960.81.060.225	A	60	-	225	200	-	-	2
2960.81.060.240	C	60	-	240	85	155	215	4
2960.81.060.250	C	60	-	250	85	165	225	4
2960.81.060.260	C	60	-	260	85	175	235	4
2960.81.060.280	C	60	-	280	85	195	255	4
2960.81.080.080	A	80	-	80	55	-	-	2
2960.81.080.100	A	80	-	100	75	-	-	2
2960.81.080.125	A	80	-	125	100	-	-	2
2960.81.080.160	A	80	-	160	135	-	-	2
2960.81.080.200	A	80	-	200	175	-	-	2
2960.81.080.225	A	80	-	225	200	-	-	2
2960.81.080.240	C	80	-	240	85	155	215	4
2960.81.080.250	C	80	-	250	85	165	225	4
2960.81.080.260	C	80	-	260	85	175	235	4
2960.81.080.280	C	80	-	280	85	195	255	4
2960.81.100.125	B	100	50	125	100	-	-	4
2960.81.100.160	B	100	50	160	135	-	-	4
2960.81.100.200	B	100	50	200	175	-	-	4
2960.81.100.240	C	100	-	240	85	155	215	4
2960.81.100.250	B	100	50	250	225	-	-	4
2960.81.100.260	C	100	-	260	85	175	235	4
2960.81.100.280	C	100	-	280	85	195	255	4
2960.81.100.300	D	100	50	300	150	275	-	5